

SAFETY WARNING & CAUTION

The "Bolt Breaker" is an ergonomically designed tool that can cleanly break off anchor bolts flush with the concrete so that the remaining part of the anchor can be smoothly patched over without any additional prep work required. By using this tool, the bolt breaking process can be done in a fraction of the time of other known methods.

This tool eliminates the need for the use of abrasive cut-off wheels, hammers or any other type of makeshift device that is normally used for this process. Each unit comes standard with two replaceable inserts (for 1/2" and 3/8" anchor bolts) and is available in either a long or short version. Custom inserts can be made per request.

SAFETY WARNING & CAUTION:

READ ALL TOOL SPECIFIC INSTRUCTIONS BEFORE USING THIS TOOL

WEAR EYE, HAND AND FOOT PROTECTION

DO NOT OVERREACH WHEN USING THIS TOOL

- Never extend the tool further than the length of your arms

KEEP PROPER FOOTING AND BALANCE AT ALL TIMES

- Never push or pull the tool with a force that would allow you to fall when the bolt breaks

RECOVER BROKEN ANCHOR BOLT AND DISPOSE OF PROPERLY

- Broken off anchor bolts create an immediate trip or fall HAZARD

**Safe
Ergonomic
Clean
and Fast**



1. Unscrew cap from top of handle.

2. Retrieve desired insert and allen wrench from inside the handle.



3. Loosen both set screws.



4. Remove existing insert from end of Bolt Breaker.

Contact info:

5. Insert desired insert.



6. Re-tighten both set screws.

Bolt Breaker Insert Change/Replacement Procedures